

CONTAINER MOISTURE ABSORBER

CONTAINER DESICCANT 750 G

Calcium chloride desiccant in Tyvek with a plastic-laminated back, 2 adhesive strips and an optional hook: lay it on top of the cargo or hang it from the container bars. Absorbs over 300 % of its weight at 60 °C and 90 % RH.

CONTAINER DESICCANT · 750 G



ABSORPTION

>300 %

60 °C · 90 % RH

ABSORPTION

≥200 %

25 °C · 80 % RH

CALCIUM CHLORIDE

80 %

Anhydrous · CAS 10043-52-4

NET WEIGHT

750 g

Blanket or hanging

COMPOSITION


COMPONENT	CAS NO.	PROPORTION
Anhydrous calcium chloride	10043-52-4	80 %
Modified starch	—	20 %

TECHNICAL REQUIREMENTS

Appearance	Clean and non-hazardous
Absorption at 25 °C · 80 % RH	≥ 200 %
Absorption at 60 °C · 90 % RH	Over 300 %
Packaging	Tyvek, leak-proof

DUAL INSTALLATION

ONE UNIT, TWO USES



01 ON THE CARGO

MAIN INSTALLATION

- Waterproof laminated back
A barrier between the blanket and your goods
- 2 adhesive strips
Stays in place, no extra fittings
- Uses the free space under the roof
Ideal when there is nowhere to hang it



02 HANGING

- Optional hook
Heavy-duty, for the container bars

CERTIFIED QUALITY

Over 3 times its weight in water (over 300 % at 60 °C and 90 % RH). Certificate of analysis with every batch.

HOW MANY DESICCANTS DO YOU NEED?

Work out the units for your container based on cargo, route and season.

[Open the calculator →](#)

Absorption capacity measured in the laboratory at 60 °C and 90 % RH. The number of units per container depends on the cargo, route and season: calculate it at secalcargo.com/en/calculators. Store in the original, closed packaging in a dry place. Specifications subject to improvement without notice.